

A

1000MET401052301

Pages: 3

Reg No.: \_\_\_\_\_

Name: \_\_\_\_\_

APJ ABDUL KALAM TECHNOLOGICAL UNIVERSITY

Seventh Semester B.Tech Degree (S, FE) Examination May 2023 (2019 Scheme)



Course Code: MET401

Course Name: DESIGN OF MACHINE ELEMENTS

Max. Marks: 100

Duration: 3 Hours

**PART A**

*Answer all questions, each carries 3 marks.*

Marks

- |    |   |     |
|----|---|-----|
| 1  | What types of stresses are induced in shafts?   | (3) |
| 2  | What is the manufacturing method for connecting rod?  | (3) |
| 3  | Why are clutches usually designed on the basis of uniform wear?   | (3) |
| 4  | What is a differential band brake?  | (3) |
| 5  | State desirable properties of a good lubricant.   | (3) |
| 6  | Enumerate the advantages of needle roller bearings.   | (3) |
| 7  | What are the advantages of 20 degree full depth involute teeth gears?                                   | (3) |
| 8  | Compare the contact between mating teeth of parallel and crossed helical gears.                         | (3) |
| 9  | What is the relationship between actual and virtual number of teeth and the pitch angle in bevel gears? | (3) |
| 10 | Why is the efficiency of worm gear drive low?   | (3) |

**PART B**

*Answer any one full question from each module, each carries 14 marks.*

**Module I**

- 11 A shaft of a motor is supported at two points which are 900 mm apart. The motor develops 20 kW at 1500 rpm. The armature of the motor can be considered as a uniformly distributed load of 15 N/mm, centrally spread over a length of 600 mm, selecting a suitable material and choosing appropriate value for the factor of safety, determining the diameter of the motor shaft. (14)

**OR**

- 12 Select a suitable flat belt for a horizontal drive for a compressor. An electric motor of 6.5 kW having a speed of 1500 rpm is used to drive the compressor. The speed of the compressor pulley is 500 rpm. Assume a service factor of 1.2, slip = 2.5 %, and working stress of 2.3 MPa. (14)

**Module II**

- 13 A single plate clutch having one pair of contacting surfaces to transmit 15 kW at 1500 rpm. The coefficient of friction between contact face is 0.35 and the permissible intensity of pressure should not exceed  $0.6 \text{ N/mm}^2$ . The outer diameter of the clutch is 300 mm. Determine the clutch dimensions by assuming uniform wear theory. (14)

**OR**

- 14 A simple band brake is to be designed to stop the rotation of a shaft transmitting a power of 50 kW at a rated speed of 600 rpm. The diameter of the drum is 600 mm, angle of contact of the band on drum is  $225^\circ$  and the total length of the lever is 1000 mm. Distance between the fulcrum and the other end of the band is 300 mm. The drum rotates in the clockwise direction and free end of the lever at the left side of the drum. Selecting suitable materials determine: (i) band dimensions, (ii) brake lever dimensions, and (iii) diameter of fulcrum pin. (14)

**Module III**

- 15 A lightly loaded 0.1 m long journal bearing is acted on by 0.6 kN radial load. The 0.07 m diameter journal is rotating at 1500 rpm. The viscosity of the oil is 3.5 cP and radial clearance of  $5 \times 10^{-5}$  m. Determine the frictional power loss using Petroff's equation. (14)

**OR**

- 16 Select suitable deep groove ball bearing for a shaft diameter of 50 mm. The shaft operates at 3000 rpm and is acted upon by steady and continuous 5000 N radial load and 2000 N thrust load. The life expectancy of the bearing is 20000 hours. (14)

**Module IV**

- 17 Design a pair of spur gear to transmit 20 kW power with velocity ratio of 4:1. The pinion is rotating at 1200 rpm. The centre distance between parallel shaft is 150 mm. The allowable static stress for pinion and gear materials are 206.3 MPa and 137.2 MPa respectively. (14)

**OR**

- 18 Design a pair of equal diameter helical gears to transmit 35 kW at 1000 rpm. The parallel shafts are 0.5 m apart. Assume the helix angle is  $30^\circ$ , pressure angle is  $20^\circ$  stub. The gear is made of steel. (14)

**Module V**

- 19 a) Under what circumstances the bevel gears are used? Give a detailed classification of bevel gears. (4)
- b) With a neat sketch explain the terminology of bevel gears. (10)

**OR**

- 20 Five kW of power at 1500 rpm is supplied to the worm shaft. The normal pressure angle is  $20^{\circ}$  degrees and coefficient of friction is 0.1. Determine the components of gear tooth force acting on the worm and worm wheel. The worm and worm gear is designated as 3/60/10/8. (14)

\*\*\*\*